



A Message from the President



Congratulations on purchasing an Anchor Audio sound system, the choice of thousands of satisfied customers including the White House, prestigious universities, school districts nationwide, police and fire departments, and all branches of the U.S. military. Our products are made of the finest materials and built with pride in the U.S.

We've incorporated the latest technology into your sound system yet kept it simple to use. Just take a few minutes to review this manual to ensure the maximum enjoyment of your Anchor system. Or, you can view a demonstration video complete with a trouble shooting section at www.anchoraudio.com.

Feel free to call our friendly customer support staff at 1-800-ANCHOR1 Monday thru Friday between 7:00am and 5:00pm Pacific Standard Time with any questions. We love to hear from our customers.

Janet Jacobs, President
on behalf of all Anchor employees

CONTENTS

GETTING STARTED	1
ARCHITECTS' SPECIFICATION / BACK PANEL	2
AN-135 TECHNICAL SPECIFICATIONS	3

GETTING STARTED

Please check your new unit carefully for any damage which may have occurred during shipment. Each Anchor product is carefully inspected at the factory and packed in specially designed boxes for safe transport.

Notify the freight carrier immediately of any damage to the shipping box or product. Repack the unit in the original box and wait for inspection by the carrier's claim agent. Notify your dealer of the pending freight claim.

NOTE: All damage claims must be made with freight carrier!

RETURNING SYSTEMS FOR SERVICE OR REPAIR

For service or repair, please contact the dealer you purchased your system from or Anchor Audio Customer Service at 800.262.4671 to obtain a RA (*Return Authorization*) number. You may also complete an online RA request form at www.anchoraudio.com. All shipments to Anchor Audio must include a RA number and must be shipped prepaid. C.O.D. shipments will be refused and returned at your expense.

IMPORTANT: Save the shipping box & packing materials, they were specially designed to ship your unit!

WARRANTY REGISTRATION

Visit our website at www.anchoraudio.com and select "Warranty Registration." Complete the online form to activate the six-year limited warranty on your AN-135 speaker monitor and two-year limited warranty for the microphones.



ARCHITECTS' SPECIFICATION

The speaker shall be an Anchor AN-135 or equivalent. The general construction shall include an injection-molded case, one 4.5" Neodymium woofer and input terminations consisting of both 3.5 mm and 1/4" phone.

The maximum speaker dimensions shall not exceed 5.25" high, 8.4" wide and 9" deep. The maximum weight shall be 3.5 pounds.

The case shall be formed by injection-molded ABS, and shall have a finish of black or white.

The speaker has the ability to be mounted on walls, ceilings, equipment racks and speaker stands with appropriate hardware and accessories.

BACK PANEL OF AN-135



LINE IN/LINE OUT
(3.5 MM)

POWER ON
VOLUME CONTROL

LINE OUT
(1/4" PHONE)

Record your presentation or "daisy-chain" another AN-135 for greater crowd coverage

NOTE: When connecting multiple AN-135 units (*daisy chaining*) stereo cable MUST be used to avoid interference.

MOUNTING BRACKETS

SB-3BK

40° tilt bracket
A multi-purpose bracket used for mounting the AN-135 to a wall or ceiling.



SB-360BK

360° swivel bracket
A multi-purpose bracket used for mounting the AN-135 to a wall or ceiling.



Waste electrical and electronic products must not be disposed of with household waste. Please recycle where facilities exist. Check with your Local Authority or Retailer for recycling advice.





SIX YEAR WARRANTY



Scan for AN-135
Technical Specs



Scan for AN-135
Brochure



Scan for AN-135
Website



Scan for How to
Videos & Articles

AN-135 TECHNICAL SPECIFICATIONS

Rated Power Output	30 Watts
Max SPL @ Rated Power	109 dB @ 1 meter
Frequency Response	65Hz - 18KHz \pm 3dB
Speaker Type	4.5" Neodymium woofer
Line Out Jack	line level, 3.5 mm – stereo
Line In Jack	line level, 3.5 mm – stereo & 1/4" phone – mono
AC Power Req.	100 - 240 VAC, 47/63 Hz (70W Max.)
Dimensions (HWD)	5.25" x 8.4" x 9" (13 x 21 x 23 cm)
Weight	3.5 lbs / 1.58 Kg



(Specifications Subject to Change Without Notice)

ANCHOR AUDIO CUSTOMER SERVICE
800.262.4671

FOR ADDITIONAL INFORMATION
visit www.anchoraudio.com