

ProLink™ Intercom Patent Pending

ProLink™ is a digital wireless intercom system that is easy to set-up and easy to operate. The system allows full duplex communication with one master belt pack and three remote belt packs without the need for a base station.

All four belt packs can communicate in "Always On" mode which is just like talking on a telephone. This allows you to continue working with your hands while using the intercom. This is particularly important for emergency response teams and evacuation coordinators. "Push to Talk" mode is also available with the flip of a switch. Applications such as directors or coaches who only want to broadcast selected instructions tend to prefer "Push to Talk."

This patent pending intercom has a range of 250' through walls and glass. The digital design and performance of ProLink will surely impress you. Take a system out for a test drive today - just email us at prolink@anchoraudio.com.



FEATURES

- Heavy Duty 4 Pin XLR Connector
- Choice of Single or Dual Muff Headsets
- A/B Channel Selection
- "Push to Talk" or "Always On" Modes
- Microphone Gain Setting
- Out of Range Indicator LED
- Low Battery Indicator LED
- Charging Indicator LED
- Rechargeable Batteries Included
- Gang Charger for Four Belt Packs
- FCC License Free
- Encryption Option Available

COMPONENTS

- BP-9000M** Master Belt Pack
- BP-9000R** Remote Belt Pack
- E-9000** Encryption Installation
- H-2000** Dual Ear Muff Headset
- H-2000S** Single Ear Muff Headset
- GC-9000** Gang Charger
- HC-1600PL** Pelican Hardcase w/
Pick 'n Pluck Foam



PACKAGE

Pro-40

Four User Package:

- 1 - BP-9000M Master Belt Pack
- 3 - BP-9000R Remote Belt Packs
- 4 - Headsets
(H-2000 or H-2000S)
- 1 - GC-9000 Gang Charger
- Lightweight, high-density card board case

TECHNICAL SPECIFICATIONS

ProLink Belt Pack (BP-9000)
RF Frequency Range 902-928MHz
Modulation FSK
Range (line of sight) Duplex 250' / 75 m
Antenna 1/2 - wavelength dipole
Power Supply 9VDC, 1.2ADC

Battery Life 15 hours
Weight 15oz. / 0.42kg (w/ batteries)
Dimensions 4.5 x 6.25 x 3.75" /
114.3 x 158.75 x 95.25 mm

Single-Ear (H-2000S) & Dual-Ear Headphones (H-2000)
Drivers Dynamic, 40mm
Impedance 300ohm +/- 15%
Frequency Response 20Hz - 20kHz
SPL 91dB +/- 3dB
Rated Power > 40mW
Distortion < 5%
Microphone Dynamic, Uni-directional,
Low impedance
Mic Sensitivity Referenced to 0dB=1V/ μ bar, 1kHz
Min -85 dB / Typical -83 dB /
Max -81 dB
Frequency Response 200Hz-12kHz
Connector Plug 4-pin XLR, female
Weight Single: 13 oz. / 0.37 kg &
Dual: 16 oz. / 0.45 kg

FCC ID: J8ZBP-9000



TWO YEAR WARRANTY



Anchor Audio, Inc.
Portable Sound Systems • Carlsbad, California

(FEATURES & SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE)

800.262.4671

www.anchoraudio.com

S-PL/0810