ANCHOR AUDIO®
TRUSTED PERFORMANCE

AN-100CM+

TECHNICAL SPECIFICATIONS

RATED POWER OUTPUT
30 Watts AC

MAX SPL @ RATED POWER
103 dB @ 1 Meter

FREQUENCY RESPONSE
65 Hz – 18 kHz ± 3 dB

MICROPHONE WIRELESS FREQUENCY
1.9 GHz DECT

MICROPHONE WIRELESS RANGE
150'+ Line of Sight

MIC INPUT
XLR

LINE IN
3.5 mm

LINE OUT
Lo-Z, Buffered, XLR and 1/4" Balanced

LINE OUTPUT LEVEL
-20 dBV (100 mVms)

SPEAKER TYPE
4.5" Woofer & 10 mm Dome Tweeter

AC POWER REQUIREMENTS
110 - 125 VAC

FUSE RATING
T 1.0A / 250 V (Internally Mounted)

EXPORT MODEL FUSE RATING
T 0.5A / 250 V (Internally Mounted)

ENCLOSURE MATERIAL
ABS Plastic

DIMENSIONS (HWD)
9" x 8.5" x 5.5" (23 x 21.6 x 14 cm)

WEIGHT
4.5 lbs / 2 Kg

WARRANTY
6 Years

Anchor Audio | 5931 Darwin Court | Carlsbad | CA | 92008 | USA | www.anchoraudio.com
@2026 Anchor Audio. All Rights Reserved.

ANCHOR AUDIO®
TRUSTED PERFORMANCE

CHM-100/DEL-100
TECHNICAL SPECIFICATIONS

POWER REQUIREMENTS
+22 VDC @ 60 mA from Pin 2 of Daisy Chain

OUTPUT IMPEDANCE
>10k

PHANTOM POWER
18 V

DAISY CHAIN IN/OUT
Male and Female 3-pin XLR

CHM-100 CONTROLS
Power, Volume, and Mute

DEL-100 CONTROLS
Power and Volume

DIMENSIONS (HWD)
6” x 7” x 3” (15.2 x 17.8 x 7.7 cm)

WEIGHT
1 lb / .45 Kg

WARRANTY
2 Years

GM-18 TECHNICAL SPECIFICATIONS

Mic Element Type
Electret Condenser (requires phantom power)

Polar Pattern
Unidirectional, Cardioid

Frequency Response
50 - 18,000 Hz

Sensitivity
-65 ± 3 dB (0 dB = 1 volt/microbar)

Output Impedance
200 ohms ± 30% at 1,000 Hz (Balanced)

Operating Voltage
12 to 48 Volts DC Phantom

Maximum SPL
110 dB

Signal-to-Noise Ratio
55 dB @ 1 kHz

Connector
3-pin Male XLR

Windscreen
Black Urethane Foam

Dimensions (HW)
18” long (457.2 mm), 0.5” (13 mm)

Weight
4.4 oz (0.12 kg)

Warranty
2 Years

Anchor Audio | 5931 Darwin Court | Carlsbad | CA | 92008 | USA | www.anchoraudio.com
@2026 Anchor Audio. All Rights Reserved.